

kona

Affordable High-Performance Multi-Purpose Cutting Plotters



A QUOI SERT UN FRIG
SI APRÈS L'AVOIR AC
ON N'A PLUS LES MOY
DE LE REMPLIR ?

Three models: 30 Inch - 55 Inch - 65 Inch



For home, office and professional users

Finest cutting quality with excellent tracking




Multi-purpose : sign cutting & lettering, contour cutting and cut through

Full-color 3.5" LCD touch screen

Newly designed sheet-off feature

Dual roll support system





NEW ! Full-Color 3.5" LCD

Kona's multi-language touch screen will allow you to change settings, launch a test cut on a new media, etc... All functionality is presented to you swiftly and elegantly.

NEW ! Dual Roll Support System

The regular media support rollers (standard on Kona 1400 and Kona 1650) allow easy vinyl handling and ensure perfect tracking.

A second optional roll-off system is available for contactless loading of pre-printed rolls. An ideal tool to avoid damage to your freshly printed rolls: no marks, no scratches.

Epos

Kona integrates a laser-based optical sensor for automatic job recognition and alignment of contour / cut through data.

NEW ! Sheet-Off System

Kona features a newly designed reliable automatic sheet-off mechanism incorporating a rotatable long-life blade with 4 cutting sides.

Specifications	KONA 760	KONA 1400	KONA 1650
Max. Media Width (roll & sheet)	39.3"	64.5"	74.4"
Max. Sheet-Off Width	29.9"	55"	64.9"
Cutting Range	4"-29.1"	4" - 54.3"	4" - 64.1"
Max. Epos Measurement Width	29.9"	55"	64.9"
Max. Speed / Acceleration	39.3"(axial) - 55.6" (diagonal) / 3 G (4.2 G diagonal)		
Cutting Force / Media Thickness	20 - 450 g / Max. 1 mm		
Stand + Wheels	Optional	Standard	Standard
Accessories	Basket, Roll-off system for pre-printed rolls		
Media Drive Mechanism	Micro-grit friction feed / Digital control servo motor		
Cutting Principle / Blade Types	Drag knife / 30° - 45° - 60° tungsten carbide blades		
Tracking	± 0.1 mm within a media moving frame of 4 metres		
Interface / Input Buffer	USB 2.0 / 40 MB		
Graphic Language	MGL		
Power Requirements	100 – 240 V AC, 50 / 60 Hz, 100 Watt		

© Copyright Mutoh Europe nv – March 2010. Specifications are liable to changes without prior notice. All trademarks mentioned are property of their respective owners.

